

5 Seconds Rapid Bactericidal



Revolutionary Ozone Spray Bottle Pro

Adding only water and with the press of one button Ideal alternative to other chemical sanitizers











Chemical-Free

The 2nd generation handheld rechargeable Professional Ozone Spray Bottle (OSB Pro) applies revolutionary electrolysis technology that can convert your regular tap water into an anti-bacterial sanitizing water. This revolutionary technology can help replace conventional chemical surface sanitizers. Simply fill the bottle with clean tap water, press the button, and the device will instantly convert ordinary water into ozonated water.

Small Size, High Performance

Ozonated water is well-known for its fast and **powerful** sanitation performance. This ozone sprayer offers an effective, safe, and environmentally friendly surface sanitation for many commercial hygiene applications.







SGS



Wayne Simmons, DMD

"My recent personal and professional practice experience utilizing aqueous ozone from BES Group has been extraordinarily positive and beneficial to our patients, our staff, and to myself. It is a remarkable technology that will be welcomed into dental practices, medical offices, hospitals, nursing facilities, food and beverage, recreational facilities, worldwide."

United States - Prosthodontist, ACP, Diplomate ABOI

With only a single press of one button

99.99%

Third-party measured sanitize rate

5 seconds **Achieve 99.99%** sanitize rate

ZERO Chemical residues 3000 times

Sanitizes faster than chlorine

25 minutes

Maintains the concentration of ozone water time

12000 times Service life



Focus Points



SARS-CoV-2



Hand sanitation



Surface sanitation



For Catering

- Hotels
- Coffee and tea : Hospitals
- Restaurants Bars



For Health Care

- Kindergartens Nursing Homes



For Public Places

- Gyms Schools
- Offices Cleaning company



Added the approval to use ozone water as a food surface bactericide in its food specification.

Only needs water and

It does not change the

USB-C charging

Two-stage mode to

Strong and sturdy

metal body

meet various applications

Plug and play

water pH

electricity No additional costs



Specifications


Model No.	EOS7161-P
O ₃ Concentration*	3.0ppm (Mode1: 5 min. & Mode2: 25 min.)
Reservoir Size	150 ml (0.04 gal); covers 30 m ²
Charging Time	60 minutes, Can generate up to 1800 ml or 12 bottles per charge
Water Quality	Clean tap water**
Water Temperature	5-35° C (41-95 °F)
Ambient Temperature	5- 40° C (41- 104 °F)
Rechargable Battery	Li-polymer Battery, 3.7V/1200mAh
Charger Input	Input : 100-240V AC, 50/60Hz Output : 5V/1A DC
Dimensions	Ф53 x 254.8 mm (Ф2.1 x 10.0 in)
Weight	308 g (0.68 lbs) ± 1%
Life Span	> 2 year (8 bottles uses/day)

^{*} Tested with soft clean water (TDS ≈ 100 ppm, temperature ≈ 25° C) Ozone concentration varies depending on conditions such as water quality or temperature.

About Us

Since 1988, BES Group has been the global leader in electrolytic technology. Converting water to ultra pure ozone gas and hydrogen gas is our core technology. Series products include Food Safety & Sanitation, Healthy Environment, Clean Water, and Sanitation & Wellness.

All products and components are tested for high performance, safety, and reliability with required certifications from government agencies and leading 3rd party labs.







Hong Kong

Biotek ozone Hong Kong limited

Room 5, 7/F, Block A, HK Industrial Centre, 489-491 Castle Peak Road, Lai Chi Kok, Kowloon.

Tel: 25626628 Fax: 30115684

https://www.biotek-ozone.com.hk





^{**}Potable water (TDS 60 - 200 ppm, Hardness < 180 ppm as CaCO₃). If hard water is used (hardness > 120 ppm CaCO₃;TDS > 250ppm), regular cleaning with citric acid solution is recommended for maintaining performance.